COMBIMASTER 350





SUBSOILER AND SEEDBED PREPARATION IN ONE







Compact 2 in 1 machine



Remediate soil compaction

Efficient seedbed preparation preventing soil sealing

WWW.VEGNIEK.NL

COMBIMASTER 350

2 IN 1 MACHINE

The CombiMaster 350 is a subsoiler and cultivator in one. Ideal for aerating the soil and preparing a perfect seedbed. Specially designed to achieve the maximum capacity with a carried machine. It is easy to mount any seed coulterbar. This makes it possible to perform 3 operations in 1 working pass without riding the ground in between. The required power and therefore fuel consumption is very low.

REMEDIATE SOIL COMPACTION

The ground is not driven upon to do another tillage after subsoiling. As a result, no tracks of vehicles are left behind and the soil is not compacted. The subsoiler and cultivator frame are individually adjustable in height to achieve the perfect working depth for the subsoiler as well for the cultivator.

EFFICIENT SEEDBED PREPARATION PREVENTING SOIL SEALING

The machine is built in such a way that a working width of 3.5 meters is possible with a transport width of 3.5 meters. By means of the integrated 4-point linkage both the trailing roller and the seed coulterbar are lifted up forward. This moves the centre of gravity forward, allowing safe transport. The trailing roller ensures a constant working depth to reduce the soil porosity and limit evaporation. The seedbed is cultivated without the topsoil becoming too fine. This way the soil will be prevented for sealing.







BENEFITS

High capacity because of 3 operations in one Maximum capacity with a carried machine Very low power required (130 HP) Can also be used solely as a subsoiler

OPTIONS

4 instead of 6 subsoiler tines and 1 straight tine in the middleExtra cultivator tines setOther types of cultivator sharesOther types of trailing rollers possible

STANDARD PROPERTIES

Working width: 3.5m Transport width: 3.5m Weight: 2350kg (without coulterbar) Tine distance subsoiler c.o.h.: 620 or 850mm Tine distance cultivator: 9 x 41cm Can also be used only as a subsoiler Working depth subsoiler: 25-50cm Working depth cultivator: 0-30cm Tine overload protection by shear bolts

TIP!

SEE HOW THE COMBIMASTER 350 WORKS? SCAN THE QR-CODE:



f in У 🖸