

# TRACK SUBSOILER

VEGNIK



LOSEN TRACKS IN THE SAME WORKING PASS



- ✓ No water in the tracks
- ✓ Cuts through the top layer without disturbing it
- ✓ Neat and robust machine
- ✓ Easy to use

## NO WATER IN THE TRACKS

By means of the Vegniek track subsoiler, the disturbing layer created by the tractor can be loosened in the same pass. This allows the water to sink and no water remains in the wheel tracks. The tines of the track subsoiler are infinitely adjustable in width from 1.5 metres to 2.25 metres so that they can always be fitted perfectly behind the wheels. The track subsoiler can be equipped with a mechanical lifting device, allowing the machine to be used individually or in combination with light machinery or front weight.

## CUTS THROUGH THE TOP LAYER WITHOUT DISTURBING IT

To prevent crop residue poaching and pulling up clods, it is possible to mount a disc coulter in front of the tine. The disc coulter cuts through crop residues and the top layer. As a result, crop residues has no chance of sticking to the tine and a breaking surface is created in the top layer, making it easier for the soil to break open. The disc coulter in combination with the pointed, streamlined tine ensure that the soil breaks open neatly and virtually no clods are pulled up.



## STANDARD

- ✓ 2.5-metre wide robust main frame
- ✓ 2 width-adjustable tines, easily adjustable without tools
- ✓ Tines infinitely adjustable centre-to-centre from 1.2 metres to 2.25 metres
- ✓ Shear bolt overload protection
- ✓ Support leg

## OPTIONS

- ✓ Mechanical lifting device
- ✓ Disc coulter set
- ✓ V-blades for levelling e.g. spray tracks
- ✓ Wider version
- ✓ Extra teeth

## STANDARD PROPERTIES

Working width: 1.5 m - 2.25 m

Transport width: 2.5 mtr

Number of tines: 2

Tines overload protection by shear bolts

Weight: 240 kg

## TIP!

SEE HOW THE  
TRACK SUBSOILER  
WORKS?  
SCAN THE QR-CODE:

