

COMBIMASTER 300

VEGNIK



SUBSOILER AND SEEDBED PREPARATOR IN ONE



Compact 2 in 1 machine



Remediate soil compaction



Efficient seedbed preparation preventing soil sealing

2 IN 1 MACHINE

The CombiMaster 300 is a subsoiler and cultivator in one. Ideal for aerating the soil and preparing a perfect seedbed. With an optional linkage it is possible to mount a seed drill. This makes it possible to perform 3 operations in 1 working pass without riding the ground in between. The required power and therefore the fuel consumption is very low.

REMEDiate SOIL COMPACTION

The ground is not driven upon to do another tillage after subsoiling. As a result, no new tracks of vehicles are being made and the soil is not compacted. The subsoiler and cultivator frame are individually adjustable in height to achieve the perfect working depth for the subsoiler as well for the cultivator.

EFFICIENT SEEDBED PREPARATION PREVENTING SOIL SEALING

The machine is compact so it can also be lifted by a (heavy) 4-cylinder tractor. The cage roll ensures a constant working depth and connection of the ground. The seedbed is cultivated without the topsoil becoming too fine. This way the soil will be prevented for sealing.



BENEFITS

- ✓ High capacity because of 3 operations in one
- ✓ Compact and very solidly built
- ✓ Very low power required (100 HP)
- ✓ Can also be used solely as a subsoiler
- ✓ More compact and centre of gravity closer to the tractor in transport position

OPTIONS

- ✓ Linkage for mechanical seed drill with link hooks and incl. top link
- ✓ Linkage for mounted seed drill (e.g. Kverneland DA)
- ✓ Extra cultivator tines
- ✓ Other types of cultivator shares
- ✓ Other types of trailing rollers possible
- ✓ Ring roller instead of cage roller
- ✓ Other types of tines



VM TINE



VR TINE



VC TINE



VV TINE

STANDARD PROPERTIES

Working width: 3 m
 Transport width: 3,22 m
 Tine distance subsoiler c.o.h.: 750 mm
 Tine distance cultivator: 9 x 35 cm
 Can also be used only as a subsoiler
 Variable adjustable depth subsoiler: 25-50 cm
 Variable adjustable depth cultivator: 0-30 cm
 Tines overload protection by shear bolts

TIP!

SEE HOW THE
 COMBIMASTER 300
 WORKS?
 SCAN THE QR-CODE:

